

KEY PLAN - BASEMENT

Scale = Normal

DEMOLITION GENERAL NOTES:

- | | |
|--|--|
| <p>A. REFER TO SPECIFICATIONS SECTION 0600 AND SECTION 0610 FOR MATERIAL REQUIREMENTS AND INFORMATION.</p> <p>B. CONTRACTOR SHALL COORDINATE ALL DEMOLITION WITH THE ENTIRE SET OF CONTRACT DOCUMENTS FOR THE PROJECT OF DEMOLITION WORK REQUIRED FOR THE PROJECT.</p> <p>C. THE CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS, DIMENSIONS AND MATERIALS REQUIRED FOR THE CONTRACTED WORK, REPORT ALL DISCREPANCIES TO THE ARCHITECT IMMEDIATELY BY LETTER AND/OR INSTALLATION.</p> <p>D. COORDINATE ALL REVENUE/RELOCATION AND/OR OPENINGS WITH OTHER ASSOCIATED TRADES.</p> <p>E. THE OWNER MAY SELECT AND PAY FOR THE DEMOLITION OF THE EXISTING CONTRACTOR'S WORK AND DELIVER TO THE OWNER'S DESIGNATED LOCATION WITHIN THE EXISTING FACILITY.</p> <p>F. CONTRACTOR SHALL PROVIDE DUST PROOF FENCING TO BE MAINTAINED AT ALL TIMES TO PREVENT DUST FROM LEAVING THE WORK AREA AND FROM OCCUPYING ADJACENT AREAS.</p> <p>G. CONTRACTOR SHALL PROVIDE HAZE IN A THIRED PRESSURE TO SCORE OF WORK AREAS AND IN DUST WILL BE TRANSMISSION TO OCCUPY AREAS. PROVIDE BARBICIDE TO CONTROL PRESSURE. DUST MONITORING SHALL BE BY OWNER. SEE SPECIFICATION 0110 INFECTION CONTROL.</p> <p>H. THE CONTRACTOR SHALL MAINTAIN THE EXISTING SYSTEM SHALL REMAIN IN OPERATION WITH THE SCORE WORK DURING THE ENTIRE CONSTRUCTION PHASE.</p> | <p>A. REFER TO SPECIFICATIONS SECTION 0600 AND SECTION 0610 FOR MATERIAL REQUIREMENTS AND INFORMATION.</p> <p>B. CONTRACTOR SHALL COORDINATE ALL DEMOLITION WITH THE ENTIRE SET OF CONTRACT DOCUMENTS FOR THE PROJECT OF DEMOLITION WORK REQUIRED FOR THE PROJECT.</p> <p>C. THE CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS, DIMENSIONS AND MATERIALS REQUIRED FOR THE CONTRACTED WORK, REPORT ALL DISCREPANCIES TO THE ARCHITECT IMMEDIATELY BY LETTER AND/OR INSTALLATION.</p> <p>D. COORDINATE ALL REVENUE/RELOCATION AND/OR OPENINGS WITH OTHER ASSOCIATED TRADES.</p> <p>E. THE OWNER MAY SELECT AND PAY FOR THE DEMOLITION OF THE EXISTING CONTRACTOR'S WORK AND DELIVER TO THE OWNER'S DESIGNATED LOCATION WITHIN THE EXISTING FACILITY.</p> <p>F. CONTRACTOR SHALL PROVIDE DUST PROOF FENCING TO BE MAINTAINED AT ALL TIMES TO PREVENT DUST FROM LEAVING THE WORK AREA AND FROM OCCUPYING ADJACENT AREAS.</p> <p>G. CONTRACTOR SHALL PROVIDE HAZE IN A THIRED PRESSURE TO SCORE OF WORK AREAS AND IN DUST WILL BE TRANSMISSION TO OCCUPY AREAS. PROVIDE BARBICIDE TO CONTROL PRESSURE. DUST MONITORING SHALL BE BY OWNER. SEE SPECIFICATION 0110 INFECTION CONTROL.</p> <p>H. THE CONTRACTOR SHALL MAINTAIN THE EXISTING SYSTEM SHALL REMAIN IN OPERATION WITH THE SCORE WORK DURING THE ENTIRE CONSTRUCTION PHASE.</p> |
|--|--|

DEMOLITION PLAN LEGEND:

- A. TEMPORARY PARTITION**
- B. TEMPORARY DOOR**


NOTES: 1. SEE MECHANICAL DRAWINGS FOR PLUMBING.

2. SEE ELECTRICAL DRAWINGS FOR POWER, LIGHTING AND COMMUNICATIONS DEMOLITION
3. SEE ASBESTOS ABATEMENT DRAWINGS FOR ABATEMENT WORK.

- [illegible]

AREAS OF WORK TO BE DONE DURING OFF HOURS. AREAS MUST BE CLEAN OF DUST AND DEBRIS DURING REGULAR HOURS.

Partial Basement Floor Demolition Plan - Area 2

[illegible]